

1. IDENTIFICATION

Product Name EQUISOL STRIP

Other Names NA
Manufacturer's Product Code STRIP

Recommended Use Floor stripper. For the removal of old paint, failed film coatings

and most solvent based finishes from exterior timber, metal, masonry and brick.

Supplier

Company Surface Logic Pty Ltd

Address 2/17 Bailey Crescent, Southport, Qld 4215

 Phone
 1300 966 322

 Website
 equisol.com.au

 Business Hours
 0403 477 772

 After Hours
 0403 477 772

Poisons Information Australia 13 11 26 New Zealand 0800 764 766

2. HAZARDS IDENTIFICATION

Physical State Liquid

Odor Typical

Classification

Acute toxicity - Inhalation (Vapors)	Category 4
ΙΛ Δ. 14Δ 1Δ. 1.Δ1412	Category 4
Skin corrosion/Inflatation (Vapors)	Category 1 Sub-category B
Dl.: : /::! - !:	Categorý 1 Sub-categorý B
Serious eye damage/eye irritation	Category
Serious eve damage/eve irritation	Catedorý 1
Corrosive to metals	Category 1
Corrosive to metals	Catedon 1

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed

Appearance Clear Brown

Signal Word Danger

Hazard Statements

Harmful if inhaled.

Causes severe skin burns and eye damage.

May be corrosive to metals.

Precautionary Statements - Prevention

Use only outdoors or in a well-ventilated area.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep only in original container.

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash contaminated clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.





Page 1 of 7



Precautionary Statements - Storage

Store locked up.

Store in corrosive container with a resistant inner liner.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Unknown Acute Toxicity

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethylene Glycol n-Butyl Ether	111-76-2	60 -100
Potassium Hydroxide	1310-58-3	0 - 10
Linear Primary Alcohol Ethoxylate	68439-46-3	1-5

^{**}If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.**

4. FIRST-AID MEASURES

First Aid Measures

Eye ContactRinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

POISON CENTER or doctor/physician.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin

with water/shower. Wash contaminated clothing before reuse.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Immediately call a POISON CENTER or doctor/physician.

Ingestion Never give anything by mouth to an unconscious person. Clean mouth with water and drink

afterwards plenty of water. Do not induce vomiting. Call a physician immediately.

Most Important Symptoms and Effects

Symptoms Causes severe skin burns and eye damage. Prolonged or repeated exposure can remove

natural skin oils and may produce irritation. Chronic exposure may cause liver, kidney

and/or blood disorders.

Indication of any Immediate Medical Attention and Special Treatment Needed

Notes to PhysicianTreat symptomatically. May aggravate pre-existing skin disorders and pulmonary diseases.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray (fog). Carbon dioxide (CO2). Water. Foam.

Unsuitable Extinguishing Media

Not determined.

Specific Hazards Arising from the Chemical

None known.

STISTIRIES SAFETY DATA SHEET



Hazardous Combustion Products

Normal products of combustion.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions. Protective Equipment and Emergency Procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental Precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See

Section 12, Ecological Information. See Section 13, Disposal Considerations, for additional

information. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Methods for Containment Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other

appropriate barriers.

Methods for Clean-Up Contain and collect with an inert absorbent and place into an appropriate container for

disposal. Dilute remaining residue with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Use personal

protection recommended in Section 8. For industrial and commercial use only. Avoid contact with skin, eyes or clothing. Wash face, hands, and any exposed skin thoroughly after handling. Take off all contaminated clothing and wash before reuse. Do not breathe

dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed and store in a cool, dry and well-ventilated place. Protect from

freezing. Keep out of the reach of children. Store locked up.

Incompatible Materials Acids. Oxidizing agents. Uncontrolled contact with water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene Glycol n-Butyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m³
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³

Appropriate Engineering Controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Ensure

adequate ventilation, especially in confined areas. Good general room ventilation (equivalent to outdoors) should be adequate under normal conditions. Eyewash

stations. Showers.



STRIP M8 Floor Stripper Revision/Review Date: 05-Jul-2023

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face ProtectionUse chemical splash goggles or glasses as necessary to prevent contact.

Skin and Body Protection Protective chemical impervious gloves of butyl rubber, nitrile rubber or PVC, chemical

resistant suit and boots.

Respiratory Protection Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation

wear respiratory protection.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash face, hands

and any exposed skin thoroughly after handling. Wash contaminated clothing before

reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Liquid Appearance Clear

AppearanceClearOdorNoneColorColorlessOdor ThresholdNot determined

Property Values Remarks • Method

pH 13.5-14.0

Melting Point/Freezing Point Not known
Boiling Point/Boiling Range ~ 101 °C / ~

Boiling Point/Boiling Range ~ 101 °C / ~214 °F
Flash Point Not applicable
Evaporation Rate Not determined

Flammability (Solid, Gas) Liquid-not applicable

Not applicable

Upper Flammability Limits

Lower Flammability Limit

Vapor Pressure

Vapor Density

Consider Considering Solid, Gas)

Liquid-not applicable

Not applicable

Not determined

Not determined

Specific Gravity 1.07

Water Solubility Completely soluble @ 25 °C (77 °F)

Solubility in other solvents Not determined **Partition Coefficient** Not determined **Auto-ignition Temperature** Not determined **Decomposition Temperature** Not determined **Kinematic Viscosity** Not determined **Dynamic Viscosity** Not determined **Explosive Properties** Not determined **Oxidizing Properties** Not determined

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children. Keep from freezing.

Incompatible Materials

Acids. Oxidizing agents. Uncontrolled contact with water.

STRIP M8 Floor Stripper



Revision/Review Date: 05-Jul-2023

Hazardous Decomposition Products

Normal products of combustion.

11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Eye Contact Causes severe eye damage.

Skin Contact Causes severe skin burns.

Inhalation Harmful if inhaled.

Ingestion May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol n-Butyl Ether 111-76-2	= 470 mg/kg (Rat)	= 2270 mg/kg (Rat) = 220 mg/kg	= 2.21 mg/L (Rat)4 h = 450 ppm(Rat)4 h
Potassium Hydroxide 1310-58-3	= 214 mg/kg (Rat)	-	-
Linear Primary Alcohol Ethoxylate 68439-46-3	= 1400 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	-

Information on Physical, Chemical and Toxicological Effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

However, the product as a whole has not been tested. Group 3 IARC components are "not

classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol n-Butyl Ether 111-76-2	А3	Group 3		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

Chronic Toxicity Chronic exposure may cause liver, kidney and/or blood disorders.

Numerical Measures of Toxicity

Not determined

Unknown Acute Toxicity

None known.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

STRIP M8 Floor Stripper



Revision/Review Date: 05-Jul-2023

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethylene Glycol n-Butyl Ether 111-76-2	-	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	-	1698 - 1940: 24 h Daphnia magna mg/L EC50 1000: 48 h Daphnia magna mg/L EC50
Potassium Hydroxide 1310-58-3	-	80: 96 h Gambusia affinis mg/L LC50 static	-	-
Linear Primary Alcohol Ethoxylate 68439-46-3	EC50: 0.95mg/L (Algae)	6mg/L (96hr) Pimephales promelas (Fathead minnow)	-	2.5mg/L (48hr) Daphnia magna

Persistence/Degradability

Not determined

Bioaccumulation

Not determined

Mobility

Chemical Name	Partition Coefficient
Ethylene Glycol n-Butyl Ether 111-76-2	0.81
Potassium Hydroxide 1310-58-3	0.83

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and

regulations.

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Potassium Hydroxide	Toxic
1310-58-3	Corrosive

14. TRANSPORT INFORMATION

Based on currently available package sizes of 5L and 15L, product is eligible for **Note**

quantity exception labelling.

UN1760, Corrosive Liquid, NOS (Containing Potassium Hydroxide), 8, PG II UN/ID No

15. REGULATORY INFORMATION

International Inventories

Canada – Domestic Substances List (DSL) TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt. All ingredients are listed or exempt.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List



US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Potassium Hydroxide 1310-58-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	Yes

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol n-Butyl Ether	111-76-2	10-30	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Potassium Hydroxide 1310-58-3	1000 lb			Х

16. OTHER INFORMATION

NFPA
Health Hazards
Not determined
HMIS
Health Hazards
3
Flammability
Not determined
Not determined
Not determined
Not determined
Not determined
Physical Hazards
Personal Protection
Not determined

Issue Date 03-Oct-2021 Revision/Review Date: 05-Jul-2023

Revision Note Version 1.2 Updated Section 14

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Keep Out of Reach of Children. For Industrial and Institutional Use Only.

Page 7 of 7